



Capacitive Sensor Series 80 - PNP



Housing M 32 x 1.5

- Capacitive sensor for level and position control
- Housing material: PTFE
- Sensing distance 1...40 mm adjustable
- With flange connector M 12 x 1



Technical data	Non-flush mountable
Operating distance S_n	25 mm
Operating distance min. / max. adjustable	1...40 mm
Electrical version	4-pin DC
Output function	Antivalent
Type PNP	KAS-80-35-A-M32-PTFE-100C-Y5-1-HP
Art.-No.	KA 0119
Operating voltage (U_B)	10...35 V DC
Voltage drop max. (U_d)	≤ 2.0 V
Permitted residual ripple max.	10 %
Operating current (I_e)	2 x 0...250 mA
No-load current (I_o)	Typ. 15 mA
Frequency of operating cycles max.	50 Hz
Permitted ambient temperature	-25...+100 °C
LED-display	Green / yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection	Flange connector M 12 x 1 (A-coded)
Housing material	PTFE (FDA 21 CFR 177.1550)
Active surface	PTFE (FDA 21 CFR 177.1550)
Lid	PC (FDA 21 CFR 177.1580)
Media optimized	Yes
Accessories (delivered with the sensor)	2 nuts M 32 x 1.5
Matching connectors (not delivered with the sensor)	#193391, #193392

* With sealed potentiometer screw



Made in Germany