



Capacitive Sensors

Series 80 - PNP



Housing 1"

- Housing material: Brass
- Sensing distance 1...40 mm adjustable
- With flange connector M 12 x 1



Technical data	Non-flush mountable
Operating distance S_n	25 mm
Operating distance min. / max. adjustable	1...40 mm
Electrical version	4-pin DC
Output	Antivalent (NO + NC)
Type PNP	KAS-80-35-A-G1-PTFE/MS-Y5-1-HP
Art.-No.	KA 0528
Operating voltage (U_B)	10...35 V DC
Operating current (I_e)	2 x 0...250 mA
Voltage drop max. (U_d)	≤ 2.0 V
Permitted residual ripple max.	10 %
No-load current (I_o)	Typ. 15 mA
Frequency of operating cycles max.	50 Hz
Permitted ambient temperature	-25...+70 °C
LED-display	Green / yellow
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67*
Norm	EN 60947-5-2
Connection	Flange connector M 12 x 1 (A-coded)
Housing material	Brass
Active surface	PTFE (FDA 21 CFR 177.1550)
Lid	PC (FDA 21 CFR 177.1580)
Media optimized	Yes
Accessories (included in delivery)	2 nuts G 1"

*with sealed potentiometer screw



Made in Germany