














## CONNECTEURS FEMELLES

Capteur	Connecteur		Code Art.	LED	IP	Raccorde- ment	Long. de câble	Long. du connect.	Version pour connexion à
	Type	No.							
pnp/npn	9		191500	-	67	4 x 0,75/ Pg 9 Bornes à vis	-	28	Y3, Y5 antivalent
AC/DC	9a		191550	-	67	4 x 0,75/ Pg 9 Bornes à vis	-	28	Y1
pnp/npn	16a		191910	-	67	4 x 0,34	5	17	Y3, Y5
pnp/npn	18		192000	-	67	3 x 0,34	5	35	Y3, Y5
pnp	21		192150	+	67	3 x 0,34	5	18	Y3, Y5
npn	22		192200						
pnp/npn	36		192900	-	67	4 x 0,25	5	31	Y3, Y5 antivalent
pnp/npn	38		193000	-	67	4 x 0,25	5	17	Y3, Y5 antivalent
pnp/npn	45		193210	-	67	3 x 0,25	5	29	Y7, Y8
pnp	46		193220	+	67	3 x 0,25	5	12	Y7, Y8
pnp/npn	47		193230	-					
pnp/npn	49a		193345	-	68	5 x 0,5	2	20	Y10
pnp/npn AC/DC	50		193350	-	67	5 x 0,25	2	18	Y1, Y9
pnp/npn	57a		193385		67	4 x 0,34	5	18	Y3, Y5 antivalent
NAMUR	58a		193386		67	2 x 0,34	5	18	Y3, Y5

Sous réserve de modification des caractéristiques sans préavis. (06/2014)