

FEMALE CONNECTORS

| Sensor | Female connector | | Article No. | LED | IP | Connection | Cable-length | Sensor + Length | Version | |
|------------------|------------------|-----|---|--------|----|------------|--------------------------------|-----------------|---------|----------------------|
| | Type | No. | | | | | | | | Fig. |
| pnp/npn | | 9 |  | 191500 | - | 67 | 4 x 0.75/ Pg 9 clampable | - | 28 | Y3, Y5 antivalent |
| AC/DC | | 9a |  | 191550 | - | 67 | 4 x 0.75/ Pg 9 clampable | - | 28 | Y1 |
| pnp/npn | | 16a |  | 191910 | - | 67 | 4 x 0.34 | 5 | 17 | Y3, Y5 |
| pnp/npn | | 18 |  | 192000 | - | 67 | 3 x 0.34 | 5 | 35 | Y3, Y5 |
| pnp | | 21 |  | 192150 | + | 67 | 3 x 0.34 | 5 | 18 | Y3, Y5 |
| npn | | 22 | | 192200 | | | | | | |
| pnp/npn | | 36 |  | 192900 | - | 67 | 4 x 0.25 | 5 | 31 | Y3, Y5 antivalent |
| pnp/npn | | 38 |  | 193000 | - | 67 | 4 x 0.25 | 5 | 17 | Y3, Y5 antivalent |
| pnp/npn | | 45 |  | 193210 | - | 67 | 3 x 0.25 | 5 | 29 | Y7, Y8 |
| pnp | | 46 |  | 193220 | + | 67 | 3 x 0.5 | 5 | 12 | Y7, Y8 |
| pnp/npn | | 47 | | 193230 | - | | | | | |
| pnp/npn | | 49a |  | 193345 | - | 68 | 5 x 0.25 | 2 | 20 | Y10 |
| pnp/npn AC/DC | | 50 |  | 193350 | - | 67 | 5 x 0.25 | 2 | 18 | Y1, Y9 |
| pnp/npn | | 57a |  | 193385 | | 67 | 4 x 0.34 | 5 | 18 | Y3, Y5 antivalent |
| NAMUR | | 58a |  | 193386 | | 67 | 2 x 0.34 | 5 | 18 | Y3, Y5 |

All specifications are subject to change without notice. (06/2014)