







FEMALE CONNECTORS

Sensor	Female connector		Article No.	LED	IP	Connection	Cable-length	Sensor + Length	Version	
	Type	No.								Fig.
pnp/npn		9		191500	-	67	4 x 0.75/ Pg 9 clampable	-	28	Y3, Y5 antivalent
AC/DC		9a		191550	-	67	4 x 0.75/ Pg 9 clampable	-	28	Y1
pnp/npn		16a		191910	-	67	4 x 0.34	5	17	Y3, Y5
pnp/npn		18		192000	-	67	3 x 0.34	5	35	Y3, Y5
pnp		21		192150	+	67	3 x 0.34	5	18	Y3, Y5
npn		22		192200						
pnp/npn		36		192900	-	67	4 x 0.25	5	31	Y3, Y5 antivalent
pnp/npn		38		193000	-	67	4 x 0.25	5	17	Y3, Y5 antivalent
pnp/npn		45		193210	-	67	3 x 0.25	5	29	Y7, Y8
pnp		46		193220	+	67	3 x 0.5	5	12	Y7, Y8
pnp/npn		47		193230	-					
pnp/npn		49a		193345	-	68	5 x 0.25	2	20	Y10
pnp/npn AC/DC		50		193350	-	67	5 x 0.25	2	18	Y1, Y9
pnp/npn		57a		193385		67	4 x 0.34	5	18	Y3, Y5 antivalent
NAMUR		58a		193386		67	2 x 0.34	5	18	Y3, Y5

All specifications are subject to change without notice. (06/2014)