

Accessories



Protection set M30 - Art.-Nr. 196302
M32 - Art.-Nr. 196301

The PTFE protection set M32 x 1.5 consists of an internally threaded cover, a Pg9-screwing for cable entry and a rubber gasket between the cover and the sensor. This protection cover serves as improvement to the degree of protection, against infiltration of liquids, for example in applications where the sensor is totally immersed in liquids. The resistance of the material still needs to be checked.

The thread of the sensor has to be sealed, for example with PTFE sealing-tape. The protection cover has to be screwed totally up to the end, and then the Pg9-screw has to be fixed.

Protection set, M30 suitable for KAS-70-26-A-M22-M30-PTFE or KAS-80-26-A-M22-M30-PTFE.

M32 suitable for KAS-70-26-A-200-PTFE-1", KAS-80-26-A-200-PTFE-1", KAS-70-26-A-200-PTFE-1"-SiEx-N or KAS-80-26-A-200-PTFE-1"-SiEx-N



Stainless steel welding nipple DN 25
Article No. 190 751

Sealing gasket
Article No. 190 752

Triclamp mounting clamp
Article No. 190 750



Stainless steel welding nipple, suitable for all our capacitive sensors KAS-70- or KAS-80-26-A-PTFE-Tri, KAS-70 or KAS-80-26-A-PTFE-Tri-100°C



Plastic tube fitting systems

PP tube da 32 SDR 11, L = 2000 mm
with already welded screw connection on one side
Article No. 196 360

PP union nut da 32 / 1 1/2"
Article No. 196 361

O-ring EPDM, suitable for union nut da 32
Article No. 196 362



Plastic tube fitting system, suitable for Type KAS-70- or KAS-80-26-A-PTFE-PFS1-Y5



Plastic tube fitting systems

PP / EPDM Screwing da 32 SDR with sealing gasket
Article No. 196 363

PP union nut da 32 / 1 1/2"
Article No. 196 361



Plastic tube fitting system, suitable for Type KAS-70- or KAS-80-26-A-PTFE-PFS2