



SMART PADDLE™

Capacitive Sensors
Series 80 - PNP

Housing G1/2"

- Housing material: LCP
- SIP / CIP 121° C
- Special version with flange. Sealing can be made with a gasket or PTFE-tape (not delivered with the sensor)
- Leakage control
- Overfill prevention



| Technical data | Non-flush mountable |
|---|------------------------------------|
| Level sensor, in contact with the product | Medium dependent adjustable |
| Sensitivity | Typ. ϵ_r 2...80 |
| Electrical version | 4-wire DC |
| Output function | Antivalent |
| Type PNP | KAS-80-P50-A-G1/2-LCP-Z02-1-HP |
| Art.-No. | KA 1237 |
| Operating voltage (U_B) | 10...35 V DC |
| Voltage drop max. (U_g) | ≤ 2.0 V |
| Permitted residual ripple max. | 10 % |
| Operating current (I_e) | 2 x 0...200 mA |
| No-load current (I_o) | Typ. 15 mA |
| Frequency of operating cycles max. | 2 Hz |
| Permitted ambient temperature | -25...+70 °C / CIP 121° C |
| LED-display | Green / yellow |
| Protective circuit | Built-in |
| Degree of protection IEC 60529 | IP 67* |
| Norm | EN 60947-5-2 |
| Connection cable | 2 m, PVC, 4 x 0.34 mm ² |
| Housing material | LCP (FDA 21 CFR 176.170(c)) |
| Active surface | LCP (FDA 21 CFR 176.170(c)) |
| Lid | PA |
| Media optimized | Yes |

Accessories (not delivered with the sensor): Varivent Adapter art.No. 196395, Welding Socket art.No. 196394 please see our selection of accessories.



* With sealed potentiometer screw

This capacitive level sensor is pre-adjusted for the detection of bulk materials with a dielectric constant ϵ_r from 2 to 80.

This fully electronic Paddle Sensor has no moving parts and is not subject to wear or tear and thus there is no down time due to false detections caused by material build-up.

Advantages SMART PADDLE:

- Sensitivity is pre-adjusted
- Measurement is independent of the mounting position
- Permitted pressure on the active area: 10 bar
- Process connection G 1/2"



Made in Germany

Level Measurement in a New Dimension:

SMARTTM PADDLE

The fully electronic paddle sensor.

This capacitive level sensor is designed for the level control of bulk materials and liquids with a dielectric constant (DC) of ϵ_r 2 to 80. It is media optimised and pre-adjusted, so that it can cover this large DC spectrum. An adjustment for the product to be detected simply is not necessary.



It cannot be easier.

The user mounts the sensor, makes the electrical connection and the sensor is ready for use.

The **SMART PADDLE** has no moving parts and is therefore not subject to wear or tear. It is ideal for applications where traditionally Rotary Switches, Vibrating Forks or Mechanical Switches are being used.




The advantages are obvious: easy installation, reliable level control and at the same time solving the well-known issues of mechanical systems being used today. No more down time due to false detections caused by material build-up, getting stuck between vibrating forks or around rotary switches, etc.

A variant with Easy Teach by Wire is an option for products where the dielectric constant is outside of the pre-set range.

The sensor's housing material, LCP, is very robust and also suitable for contact with food products.

The sensor has a G 1/2 inch process connection which can be used with a large range of accessories like welding brackets or „Varivent N DN 50“ flanges that are offered by Rechner.

RECHNER SENSORS is your specialist for level control!



Made in Germany

All specifications are subject to change without notice. (08.09.2020)