

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx BVS 10.0087X

Issue No: 1

Certificate history:

Status:

Current

Issue No. 1 (2019-02-25) Issue No. 0 (2010-11-24)

Page 1 of 4

Date of Issue:

2019-02-25

Applicant:

Rechner Industrie-Elektronik GmbH

Gaußstraße 8 – 10 68623 Lampertheim

Germany

Equipment:

Transmitter Supply Unit type N-132 / * / 4-20-IL

Optional accessory:

Type of Protection:

Equipment protection by intrinsic safety "i", Equipment protection by type of protection "n"

Marking:

Ex nA nC [ia Ga] IIC T4 Gc

[Ex ia Da] IIIC

Approved for issue on behalf of the IECEx

Certification Body:

Jörg Koch

Position:

Head of Certification Body

Signature:

(for printed version)

Date:

().(,

- 1. This certificate and schedule may only be reproduced in full.
- 2. This certificate is not transferable and remains the property of the issuing body.
- 3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

DEKRA Testing and Certification GmbH
Certification Body
Dinnendahlstrasse 9
44809 Bochum
Germany





Certificate No:

IECEx BVS 10.0087X

Issue No: 1

Date of Issue:

2019-02-25

Page 2 of 4

Manufacturer:

Rechner Industrie-Elektronik GmbH

Gaußstraße 8 – 10 68623 Lampertheim

Germany

Additional Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2011

Explosive atmospheres - Part 0: General requirements

Edition:6.0

IEC 60079-11: 2011

Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

Edition:6.0

IEC 60079-15: 2010

Explosive atmospheres - Part 15: Equipment protection by type of protection "n"

Edition:4

This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

DE/BVS/ExTR10.0116/01

Quality Assessment Report:

DE/BVS/QAR07.0008/09



Certificate No:

IECEx BVS 10.0087X

Issue No: 1

Date of Issue:

2019-02-25

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

Description

The Transmitter Supply Unit type N-132 / * /4-20-IL is an associated apparatus per IEC 60079-11 and has to be installed outside the hazardous area or in an enclosure which is in accordance with IEC 60079-15. It serves as 24 V power supply and signal evaluation of 2- and 3-wire transmitters and has to be used for signal evaluation of active current sources. Additionally the bi-directional transmission of a superimposed frequency-shift-keying signal as per HART protocol is possible.

Type designation

See Annex

Parameters

See Annex

SPECIFIC CONDITIONS OF USE: YES as shown below:

- 1 For installation of the Transmitter Supply Unit type N-132 /* / 4-20-IL in areas, where EPL Gc equipment is required, the apparatus has to be mounted inside an enclosure which is in accordance with IEC 60079-15.
- 2 For the application of the Transmitter Supply Unit type N-132 / * / 4-20-IL in an ambient temperature of less than 20 °C suitable cable and cable entries for this condition shall be used.



Certificate No:

IECEx BVS 10.0087X

Issue No: 1

Date of Issue:

2019-02-25

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

- The apparatus can be used in an ambient temperature range from -40 °C to +70 °C independent from the mounting position.
- Assessment of Transmitter Supply Unit in accordance with the newer standard versions.

Annex:

BVS_10_0087x_Rechner_Annex_issue1.pdf