



L&V&L Capacitive Filling Level Probe Analogue current output 4...20 mA


- Integrated evaluation electronics
- EasyTeach by wire
- Housing material: PTFE, Ø 16 mm
- Automatic identification of NPN / PNP function




Technical data	
Active zones [mm]	118 mm
Electrical version	4-wire DC
Output function	Analogue
Type	KFI-1-248-118-PTFE-D16-IL4-ETW-Z02
Art.-No.	KI 0121
Operating voltage (U _B)	15...30 V DC
Permitted residual ripple max.	5 %
Load resistance (R _L)	≤ 400 Ω
Power consumption (outputs no-load)	0,9 W
Analogue output	4...20 mA
Permitted ambient temperature	-25...+70 °C
LED-Display	Green
Protective circuit	Built-in
Degree of protection IEC 60529	IP 67
Norm	EN 60947-5-2*
Connection cable	2 m, PVC, 5 x 0.34 mm ²
Housing material	PTFE (FDA 21 CFR 177.1550)
Active zone	PTFE (FDA 21 CFR 177.1550)
Lid	PC (FDA 21 CFR 177.1580)
Accessories for mounting (is not delivered with the probe) please see our selection of accessories.	

EasyTeach chart:

- LED green / Adjustment function
- Adjustment Min.
 - Adjustment Max.
 - Factory set
 - Test



Other housing materials for the active zone (probe), like PE, GFK, PVDF or PEEK on request.



*Where applicable

Made in Germany

All specifications are subject to change without notice. (16.07.2019)